

1.

(),

60
75 %.

0 6 °

15
4 ± 2 ° .

2.

2.1.

1

	40±5			« Mitutoyo» =(23±2)° , =(50±5)%RF
	-40° ... +110 °	°		
	2-10 2-10	%		80°
	25	/ °*24		=25±2° , =(50±5)%RF
	3,5 5,0		14236	«Zwick/Roell Z 2.5», V=100 / , =(23±2)° , =(50±5)%RF
	70 40	%	14236	
	±2,5	%		

POLY-PACK

2.2.

2.2.1.

2.2.2.

2.2.3.

1

3.

: 40 – 80

« - »

« - »

2

				max,
40	30	42	1260	6 (8)
45	30	33	990	6 (8)
50	25	30	750	6 (7)
55	30	23	690	5 (6)
60	30	18	540	5 (6)
65	30	16	480	5 (6)
70	25	16	400	5 (6)
75	30	12	360	4 (5)
80	30	10	300	4 (5)

1 6.

4.

4.1.

4.1.1.

(25° , 50-60%),

4.1.2.

POLY-PACK

4.1.3.

4.1.4.

4.1.5.

4.1.6.

4.2.

20°

- 30
- 60

4.3.

10 %

() ,

4.4.

6 – 10 %

4.5.

4.5.1.

50 – 55 °

– 50, 60, 70°
(72 °

10 - 15)).

15 – 20° ,

5 - 8° .

(72 °

10 - 15)).

POLY-PACK

60	:				
-55°		100%	- 15	.	
-65°		100%	- 15	.	
-75°		100%	- 25	.	60°
-80°		100%	72°	.	
-			55 – 60°	,	
-					;
-					60°

4.6.

– 25 – 35° . ()

,

.

.

,

.

4.7.

- (,) .

5.

- 3